



NON METALIC FLOOR HARDENER









DESCRIPTION

Power grace floor hardener is ready blend of metallic nonmetallic inert high quality aggregates and cement which applied dry shake to the concrete surface. it provide protection to floor against wear impact and abrasion. Being nonmetallic power grace floor hardener non slip surface which will never rust and disintegrate.

FEATURES & BENEFITS

- · High abrasion surface does not rust or stain
- Higher resistance to abrasion wear and impact
- Free from dusting easily cleaned and attractive floor
- Maintenance free and long life performance

AREA OF APPLICATIONS

- · Loading bays
- Trucking lanes
- Car parking
- Heavy duty workshops
- · Machine shops,
- Warehouse
- Helipad
- Air craft hangers

METHOD OF APPLICATION

Power grace non metallic floor hardener mixing with water applied two coats

20kg | 40kg (G)

Using to a dry shake method of uniformly broadcasting the product onto surface of the freshly placed concrete,

-3.5 to 5.0 kg/m2

-5.0 to 7.5 kg/m2

Broadcast 2/3 of floor hardener nonmetallic onto the fresh concrete surface float the broadcasting material into the surface with mechanical or manual float after the hardener achieves a uniform moistened appearance do not use the steel trowel ..

When the water sheen has again disappeared broadcast the reaming 1/3 of the floor hardener nonmetallic onto the surface. float the concrete surface has achieved proper firmness processed with normal finishing procedures do not over trowel

COVERAGE

As per site condition coverage depend

Light to moderate duty on floor -2.5 to 3.5 kg/m2

Moderate to heavy duty floor

• Moderate to Heavy duty Hoor

Super heavy duty

SHELF LIFE

12 months from the date of manufacturing in unopened conditions STORAGE IN COOL & DRY PLACE

POWERGRACE INDUSTRIES ITO

SAFETY PRECAUTIONS

Use rubber hand gloves & safety goggles while using power grace floor hardener In case of contact with skin, wash with fresh water, Keep out of reach of children

CLEAN UP

Immediately after use equipment and tools should be cleaned with clean water

PACKAGING

20 KG ,40 KG

305, Dev Arc, Opp. Iscon Temple, S.G. Highway, Ahmedabad-380015. Gujarat. India. CIN: U85100GJ2013PLC075582 For inquiry & Feedback:
Toll Free: 1800 121 0141
E-Mail: care@powergraceindustries.com,
Web: www.powergraceindustries.com