



POWER MASTIC









DESCRIPTION

Two pack mastic for marble and stone based on unsaturated polyester resins, It hardens quickly adding its hardener. It has good adhesive power, its fluidity allows penetrating in the hollowness and porosity of the stone. After hardening, it can be worked as the stone. It can be coloured using paste colouring tubes and colouring oxide powders; It is resistant to the most of chemical products such as oils, fats,

APPLICATION AND ITS USAGE

• Mix the mastics with hardener in required proportion and apply the mixture by putty blade on the joints, cracks & holes (for colour matching mix proportionate amount of colour pigment.)

INSTRUCTION TO USE

- 1. The area to be glued or filled must be clean, perfectly dry and dust free.
- 2. Add 2% paste hardener in weight to the mastic, mix thoroughly until a homogenous mass is obtained and apply with a spatula on horizontal or vertical surface
- 3. In cold season the hardener may increase up to 3%
- 4. Once hardened after a couple of hours, the mastic can be grinded and polished
- 5. For materials with porosity or holes very big(travertine), we suggest to make a second application

SUGGESTION FOR USE

- 1. Do not use the hardener more than 4% as it will reduce adhesion of the product, It also reduces time and could case a variation
- 2. Never mix the total quantity of the mastic at one time in order to avoid, 'Mass effect' because the mastic will dry quickly too.
- 3. Do not use hardener in quantity less than 1% and / or at low temperature below 5 o C, which catalysing time very long.

ADVANTAGES

Makes applied area water proof
Weather proof
Flake resistant
Making the joints as invisible joints.

AVAILABLE IN

2 Colours in semi solid & Liquid form

COLOURS

Cream, White, Transparent & Crystalline

PACKING

1 kg|5kg|10kg|20kg

SOLUTION FOR

Fill cracks and holes, and also repair joints



1 kg | 5kg | 10kg | 20kg

305, Dev Arc, Opp. Iscon Temple, S.G. Highway, Ahmedabad-380015. Gujarat. India. CIN: U85100GJ2013PLC075582